

**CARL TURNER EQUIPMENT INC.**

**LIFT PRE-INSTALLATION CHECKLIST**

SALES REP \_\_\_\_\_.

CUSTOMER: \_\_\_\_\_ ADDRESS: \_\_\_\_\_

CITY, ZIP: \_\_\_\_\_

PHONE #: \_\_\_\_\_ CONTACT: \_\_\_\_\_

**LIFT SPECS**

MODEL(S): \_\_\_\_\_

QUANTITY: \_\_\_\_\_

**SERVICE BAY(S) SPECS**

CEILING HEIGHT \_\_\_\_\_ FT \_\_\_\_\_ IN

BAY WIDTH \_\_\_\_\_ FT \_\_\_\_\_ IN

BAY LENGTH \_\_\_\_\_ FT \_\_\_\_\_ IN

**IMPORTANT QUESTIONS**

1.) CONDITION OF CONCRETE \_\_\_\_\_ FAIR \_\_\_\_\_ POOR \_\_\_\_\_ GOOD  
DETAILS \_\_\_\_\_

2.) CRACKS OR SEAMS \_\_\_\_\_ YES \_\_\_\_\_ NO ( COLUMNS MUST BE 6" FROM  
ANY SEAM OR CRACK)

3.) IS THERE A SLOPE? \_\_\_\_\_ YES \_\_\_\_\_ NO ( STANDARD SHIMS ONLY  
ACCOMMODATE A 1/2" SLOPE – FULL CONTACT SHIMS EXTRA)

4.) DEPTH OF CONCRETE. \_\_\_\_\_ ( MINIMUM 4" @ 3000 PSI)

5.) CEILING OBSTRUCTIONS. \_\_\_\_\_ YES \_\_\_\_\_ NO

EXPLAIN \_\_\_\_\_

6.) IS THERE ELECTRICITY (110V) WE CAN PULL FROM TEMPORARILY TO TEST THE LIFT? \_\_\_\_\_ YES \_\_\_\_\_ NO

7.) IS THERE AN AIR SUPPLY NEAR THE BAY(S)? \_\_\_\_\_ YES \_\_\_\_\_ NO

8.) ARE THERE ANY OBSTRUCTIONS FOR UNLOADING \_\_\_\_\_ YES \_\_\_\_\_ NO

9.) WILL LIFT BE LOCATED OUTSIDE? \_\_\_\_\_ YES \_\_\_\_\_ NO

**IMPORTANT NOTICE:**

**THE FLOOR ON WHICH THE LIFT IS TO BE INSTALLED MUST BE 4" MINIMUM THICKNESS OF CONCRETE, WITH A MINIMUM COMPRESSION STRENGTH OF 3000 PSI AND REINFORCED WITH STEEL MESH OR BAR AS PER COMMERCIAL PRACTICE. IF CONCRETE PADS ARE POURED IN PLACE OF A STANDARD SLAB THEY MUST BE 4' X 4' X 1' THICK. PADS MUST BE REINFORCED WITH STEEL PER COMMERCIAL PRACTICE WHEN ON ASPHALT OR DIRT BASE.**

**FAILURE BY PURCHASER TO PROVIDE THE RECOMMENDED MOUNTING SURFACE COULD RESULT IN UNSATISFACTORY LIFT PERFORMANCE, PROPERTY DAMAGE AND OR PERSONAL INJURY.**

**IT IS THE RESPONSIBILITY OF THE PURCHASER TO INFORM INSTALLERS OF ANY WIRING AND/OR PLUMBING UNDER CONCRETE PRIOR TO INSTALLATION. CARL TURNER EQUIPMENT ASSUMES NO LIABILITY FOR DAMAGE TO PLUMBING AND/OR ELECTRICITY UNDER CONCRETE. INSTALLATION DOES NOT INCLUDE ELECTRICAL OR PLUMBING.**

**FOR DIRECT SHIPMENTS: CUSTOMER IS RESPONSIBLE FOR THE UNLOADING OF LIFT(S) UNLESS PRIOR ARRANGEMENTS HAVE BEEN MADE.**

I HAVE READ THE PREVIOUS NOTICE REGARDING INSTALLATION REQUIREMENTS

PURCHASER \_\_\_\_\_

**PLEASE ENSURE THAT BAY IS CLEAR PRIOR TO INSTALLATION**

**PLEASE REFER ALL INSTALLATION INQUIRIES TO:**

**JASON HASHLEY  
SERVICE DIRECTOR**